

Novintaab LED Wallwasher

15W

Specification



A/A+ Serie

POWER LED Module

Internal Close Current Switching Driver

Poly Acrylic Glass

Aluminium Anodized Body

Very Low Weight Body With IP65

Optional Input 12/24 Vdc & 220AC 50Hz



distance(cm)	cone diameter	E(lx)
100.0	54.2	E(0°) 6330
200.0	63	E(0°) 1582
300.0	72	E(0°) 703
400.0	80.5	E(0°) 395
500.0	89.2	E(0°) 253
600.0	97.5	E(0°) 175

half value angle 5°

15W Wallwasher

Parameter	A	A+
Input Voltage	AC 110~240V	AC 110~240V
Frecuency Range	50~60Hz	50~60Hz
Total Power of LED	15W	15W
LED Luminous Efficiency	100-105 Lumen/watt	120-130 Lumen/watt
LED Initial Flux	>1500	>1800
Lux @ 1m	4800 Lux	6330 Lux
Average Illumination Mounting Hight: 6 meters	126-139 Lux	167-184 Lux
Effective Illuminated Mounting Hight: 6 meters	0.95*0.95 m2	0.95*0.95 m2
Color Temperature	2000-6000K Optional	2000-6000K Optional
Color Rendering Index (CRI)	Ra>75	Ra>75
Junction Temperature	<70 °C	<70 °C
IP Rating	IP 65	IP 65
Life Span	>30000 hours	>30000 hours
Body Material	Aluminium Anodized	Aluminium Anodized
Weight	0.595 (Kg)	0.595 (Kg)
Size	455(L)*50(W)*47(H) mm	455(L)*50(W)*47(H) mm

@novintaab

novintaab

www.novintaab.com

