

Novintaab LED Wallwasher

6W

Specification



A/A+ Serise

POWER LED Module

Internal Close Current Switching Driver

Poly Acrylic Glass

Aluminium Anodized Body

Very Low Weight Body With IP65

Optional Input 12/24 Vdc & 220AC 50Hz



distance(cm)	cone diameter	E(lx)
100.0	28.7	E(0°) 2532
200.0	37.5	E(0°) 630
300.0	46.5	E(0°) 276
400.0	55	E(0°) 156
500.0	63.7	E(0°) 96
600.0	72	E(0°) 66

half value angle 5°

6W Wallwasher

Parameter	A	A+
Input Voltage	AC 110~240V	AC 110~240V
Frecuency Range	50~60Hz	50~60Hz
Total Power of LED	6W	6W
LED Luminous Efficiency	100-105 Lumen/watt	120-130 Lumen/watt
LED Initial Flux	>600	>720
Lux @ 1m	1920 Lux	2532 Lux
Average Illumination Mounting Hight: 6 meters	51-56 Lux	67-73 Lux
Effective Illuminated Mounting Hight: 6 meters	0.7*0.7 m2	0.7*0.7 m2
Color Temperature	2000-6000K Optional	2000-6000K Optional
Color Rendering Index (CRI)	Ra>75	Ra>75
Junction Temperature	<70 °C	<70 °C
IP Rating	IP 65	IP 65
Life Span	>30000 hours	>30000 hours
Body Material	Aluminium Anodized	Aluminium Anodized
Weight	0.29 (Kg)	0.29 (Kg)
Size	200(L)*50(W)*47(H) mm	200(L)*50(W)*47(H) mm

@novintaab

novintaab

www.novintaab.com

